






REV.	ECN NO.	LOCAS.	DESCRIPTION	DATE	DESIGN
A			NEW DRAWING		



PC BOARD LAYOUT



NO. of Contacts (n)	Dimensions		
	A	B	C
004	3.0	5.07	7.8
005	4.0	6.07	8.8
006	5.0	7.07	9.8
007	6.0	8.07	10.8
008	7.0	9.07	11.8
009	8.0	10.07	12.8
010	9.0	11.07	13.8
011	10.0	12.07	14.8
012	11.0	13.07	15.8
013	12.0	14.07	16.8
014	13.0	15.07	17.8
015	14.0	16.07	18.8
016	15.0	17.07	19.8
017	16.0	18.07	20.8
018	17.0	19.07	21.8
019	18.0	20.07	22.8
020	19.0	21.07	23.8
021	20.0	22.07	24.8
022	21.0	23.07	25.8
023	22.0	24.07	26.8
024	23.0	25.07	27.8
025	24.0	26.07	28.8
026	25.0	27.07	29.8
027	26.0	28.07	30.8
028	27.0	29.07	31.8
029	28.0	30.07	32.8
030	29.0	31.07	33.8
031	30.0	32.07	34.8
032	31.0	33.07	35.8

Electrical

Voltage:50 V AC(rms)/DC
Current:1A AC(rms)/DC
Contact Resistance:40 mΩ max(initial)
Dielectric Withstanding Voltage:200 V AC/rms
Insulation Resistance:800 MΩ min
Operating Temp:-40℃~+85℃

DESIGN:		Xiping Huang			广东国连电子有限公司				
CHECK:		Ke Tian			GUANGDONG GUOLIAN ELECTRONICS CO.,LTD				
APPROVED:		Youquan Xu		TITLE:					
DIM	TOL	DIM	TOL	1.0双面贴卧贴超薄H2.0					
X.	±0.25	X°	±3.0°	PART NO.					
X.X	±0.20	X.X°		1.0-CB-NPWB					
X.XX	±0.15	X.XX°		REV. A		SCALE: N/A	UNIT: mm	SHEET: 1/1	
X.XXX		X.XXX°							