

REV.	ECN NO.	LOCAS.	DESCRIPTION	DATE	DESIGN
A			NEW DRAWING		

技术参数:

- 1、所有材料符合ROHS2.0/REACH要求。
- 2、额定电流：1A，AC，DC；
- 3、额定电压：50V，AC，DC；
- 4、温度范围：-25℃~+85℃；
- 5、接触电阻：≤0.02Ω；
- 6、绝缘电阻：≥500MΩ；
- 7、耐压：500V，AC/minute.
- 8、适用线规：AWG#32 to #26
- 9、产品料号：

A15001 - n A - 02 T1

孔位

产品类型

A:直针针座

电镀

T1:镀亮锡

胶芯材质

O2:PA66 米色

Circuits	Dimensions (mm)		
	A	B	C
02	1.50	3.60	4.50
03	3.00	5.10	6.00
04	4.50	6.60	7.50
05	6.00	8.10	9.00
06	7.50	9.60	10.50
07	9.00	11.10	12.00
08	10.50	12.60	13.50
09	12.00	14.10	15.00
10	13.50	15.60	16.50
11	15.00	17.10	18.00
12	16.50	18.60	19.50
13	18.00	20.10	21.00
14	19.50	21.60	22.50
15	21.00	23.10	24.00
16	22.50	24.60	25.50

2	端子 Contact	黄铜 Brass	n*1	电镀(锡): 整个表面镀底镍30u"MIN,再镀锡80u".MIN.
1	基座 Wafer	PA66 (UL94V-0)	1	米色
序号	名 称	材 料	数 量	附 注

DESIGN:		Xiping Huang			广东国连电子有限公司					
CHECK:		Ke Tian			GUANGDONG GUOLIAN ELECTRONICS CO.,LTD					
APPROVED:		Youquan Xu		TITLE:						
DIM	TOL	DIM	TOL	ZH1.5直针针座						
X.	±0.25			PART NO.						
X. X	±0.20	X°	±3.0°							
X. XX	±0.15	X. X°		A15001-nA-02T1						
X. XXX		X. XX°								
		X. XXX°		REV.	A	SCALE:	N/A	UNIT:	SHEET:	
								mm	1/1	

